

```

1  #!/usr/bin/perl -w
2  #
3  use strict;
4  use warnings;
5  use CGI;
6
7  my $cgi = CGI->new();
8  my @qsnames;
9  my $qsindex=0;
10
11 open ( LOGFILE, ">/tmp/qs-new-name.log" ) or die "$!";
12 print LOGFILE "Logfile Begins: \n";
13
14
15 print $cgi->header('text/html');
16 # print $cgi->start_html('qsdump.cgi');
17
18
19 @qsnames = $cgi->param;
20
21
22 foreach(@qsnames)
23 {
24 # print "Element $qsindex: $_ = " . $cgi->param($_) . "<br>";
25 print LOGFILE "Element $qsindex: $_ = " . $cgi->param($_) . "\n";
26 # print "$_ <br>";
27 # print $cgi->param($_);
28 $qsindex ++;
29 }
30
31 print <<END_HTML;
32 <SCRIPT LANGUAGE="JavaScript" SRC="/tgdialer/functions.js">
33 </SCRIPT>
34
35 <TABLE WIDTH=100% BORDER=1 CELLPADDING=4 CELLSPACING=3 STYL
E="">
36 <TR VALIGN=TOP>
37 <TD WIDTH=>
38 Enter A Name For The New Campaign.
39 </TD>
40 </TR>
41 </TABLE>
42 <HR>
43 <FORM id="CampaignNameForm" name="NameForm" action="" enctype="mult
ipart/form-data" method="post">
44 <TABLE WIDTH=60% BORDER=1 CELLPADDING=4 CELLSPACING=3 STYLE
="">
45 <TR VALIGN=TOP>
46 <TR>
47 <TD WIDTH=>
48 <input type="text" name="NewCampaignName" i
d="CampaignName" size="20" >
49 New Campaign Name
50 </input>
51 </TD>
52 </TR>
53
54 </TABLE>
55 <br>
56 <br>
57 </FORM>
58
59 <input type="button" onclick="MakeNewCampaign('/cgi-bin/tgd
ialer/cgi-bin/make-new-campaign.cgi?CampaignName=Dialer_' )" id="CreateButton" tabI
ndex="" value="Create Campaign"></input>
60
61 END_HTML
62
63

```

```
64
65
66 print $cgi->end_html;
67 close LOGFILE;
```